



# Point of Use Electric Tankless Water Heaters

## EASY TO INSTALL

- Compact size for installations with space constraints
- Wall mount vertically or horizontally
- ¾" NPT water connections (1/2" NPT reducers included)

## DRY-FIRE PROTECTION

- Prevents element failure due to dry-fire
- Internal air bypass
- Temporary shutoff with excess air in chamber

## SCALE-REDUCTION TECHNOLOGY

- Reduces failures and service requirements due to scale build-up
- Power-sharing technology reduces scale deposits on elements
- Dupont™ Zytel® chambers resist scale buildup

## DIGITAL USER INTERFACE (2-CHAMBER MODEL)

- Easy temperature adjustment
- Error codes are clearly displayed

## WARRANTY

- 6-year limited chamber warranty
- 1-year limited parts warranty



SPECIFICATIONS												
Model	Series	Input		Amp Load	Recommended Breaker Size	Recommended Wire Gauge	Activation GPM	Flow Rate at 70°F Rise	Height	Depth	Width	Shipping Weight
		WATTS	VOLTS	AMP				GPM (LPM)	A IN (CM)	B IN (CM)	C IN (CM)	LB (KG)
<b>SINGLE CHAMBER, SINGLE ELEMENT MODELS</b>												
SSET-70E	100	7,000	240	29	40 Amp	8	0.25	0.7 (2.6)	15 ½ (39)	6 ½ (17)	7 (18)	9 (4)
SSET-90E	100	9,000	240	38	50 Amp	8	0.25	0.9 (3.4)	15 ½ (39)	6 ½ (17)	7 (18)	9 (4)
<b>TWO CHAMBER, TWO ELEMENT MODEL</b>												
SSET-180E	100	18,000	240	94	50 Amp x 2	8	0.25	1.8 (6.8)	16 ⅝ (42)	11 ½ (29)	6 ⅛ (16)	20 (9)